



BUS-STOP

The Air-Con Leak Sealer
For Coach and Bus

These additives are designed to remove moisture and seal small leaks in air-conditioning systems, provided that the leaks are small enough to fit within the limitations of the product. Bus-Stop is not a substitute for a professional repair but will help to reduce refrigerant loss and prolong system efficiency.

INSTRUCTIONS

Professional use only

Always use safety goggles and protective gloves

Step 1

- 1) Ensure the A/C system is fully charged first.
- 2) Connect the hose to the Dry R can.
- 3) Connect the LP automotive coupler to the low side connector on the vehicle.
- 4) If possible evacuate or purge the hose to remove any air.
- 5) Screw the tap "in" to pierce the can.
- 6) Hold the can upside down and slowly unscrew the tap to allow refrigerant into the can. *The can will become warm when it mixes with the contents.*
- 7) Screw the tap back in.
- 8) Start the vehicle and engage the A/C system.
- 9) Holding the can upside down slowly unscrew the tap and shake the can to determine when it is empty.
- 10) Remove the hose from the vehicle and allow the system to run for a few minutes.
- 11) Recover any excess refrigerant from the can and remove the hose.

Step 2

- 12) Connect the hose to the Airco Seal Pro can.
- 13) Stop the vehicle engine.
- 14) Connect the LP automotive coupler to the low side connector on the vehicle.
- 15) If possible evacuate or purge the hose to remove any air.
- 16) Screw the tap "in" to pierce the can.
- 17) Hold the can upside down and slowly unscrew the tap to allow refrigerant into the can. *The can will become warm when it mixes with the contents.*
- 18) Screw the tap back in.
- 19) Start the vehicle and engage the A/C system.
- 20) Holding the can upside down slowly unscrew the tap and shake the can to determine when it is empty.
- 21) Remove the hose from the vehicle and allow the system to run.
- 22) Recover any excess refrigerant from the can and remove the hose.

Step 3

- 23) Immediately repeat Step 2 using the next can of Airco Seal pro.

Step 4

- 24) Run the A/C for 30 minutes and check for leaks.

For any further advice contact:

JAVAC UK
6 Drake Court
Britannia Park
Middlesbrough
TS2 1RS
01642 232880
sales@javac.co.uk