

# JAVAC

## ALTIMA A2L

The JAVAC ALTIMA A2L recovery unit is the fastest recovery unit in the market. With its spark proof design it is truly a multi-purpose recovery unit, suitable for a whole range of CFC's, HCFC's and HFC's with blends and A & B variations as well as A2L flammable refrigerants such as R32, R1234yf and R1234ze.

### FEATURES AND BENEFITS

Some of the special features of the ALTIMA include a heavy duty twin head 3/4 HP high torque AC motor, allowing for market leading recovery rates. Its spark proof design boasts UL listed ignition protected switch and circuit breaker along with a 5m hard wired 240V lead. The ALTIMA includes a comprehensive built in manifold analyser. Purge and selfcleaning is "on the fly" so there is no need to shut down. You can push, pull and sub cool by using this advanced facility. Built in safety features include; cool to touch, refrigerant connections that point down away from your eyes, safety switches, thermal overloads, circuit breakers and convenient connection points all on one side of the unit. Overall, the ALTIMA is ergonomically designed, making this unit easy to carry. Like all of JAVAC's products, it is built to stringent standards for quality.



### TECHNICAL SPECIFICATIONS

- Recovery Rates: Liquid 216kg / hr  
Vapour 30kg / hr  
Push Pull 660kg / hr
- Size: L 420mm  
W 290mm  
H 420mm
- Weight: 16kg
- Twin head 3/4 HP compressor
- Oil free compressor
- Automatic shut off
- Integrated self purge
- High power fan cooling
- Integrated low pressure control
- Low pressure control manual override
- HP and LP gauge fully enclosed
- Integrated circuit breaker protection
- High capacity condenser
- Connection fittings 1/4 SAE

Part Number	XTRC2-A2L
-------------	-----------



For more information speak to JAVAC today!

Vacuum and Refrigeration Process Technology  
01642 232880 – [www.javac.co.uk](http://www.javac.co.uk)  
[sales@javac.co.uk](mailto:sales@javac.co.uk)

