

REFMATE

(2 & 4 VALVE DIGITAL MANIFOLD)

With state-of-the-art technology and tried-and-tested features the REFMATE-2 has benefits in daily use. Instead of a touch display, the REFMATE has sturdy, intuitive buttons and an easy-to-read colour display with an analogue pointer. It's practical too – the REFMATE can be locked for long-term measurements on construction sites. Supplied with 60" RYB hoses with or without CA valves stored in a sturdy plastic carry case.



Intuitive button control

Large 4.3 inch TFT colour display

Sight Glass

- Patented analogue display with pointers
- Superheat and subcool indicator
- High precision with class 0.5 accuracy
- Flexible power source (AA batteries or USB)
- Wireless communication with app and other devices
- Lockable for long-term measurements

2
YEAR
GUARANTEE

5★
SERVICE &
SUPPORT


CALIBRATION
SERVICE
AVAILABLE

V1 06/19

REFMATE (2 & 4 VALVE DIGITAL MANIFOLD)



PRODUCT SPECIFICATIONS

Pressure sensor range	0.95 to 60 bar
Max. working pressure	60 bar
Max. overpressure	80 bar
Operating temperature range	-40°C to +125°C / -40°F to +257°F
Accuracy	±0.5% (class 0.5)
Resolution	0.01bar / 0.5psi / 1kPa / 0.001MPa / 0.01kg/cm2
External temperature sensors connector	K-type
Weight	1.15 kg
Device dimensions	200(H) x 190(W) x 75(D) mm

PRODUCT VARIANTS

Product	K Type temperature sensors	5-piece hose set	Special vacuum hose 3/8"	Temp clamps	Case	Part No.
REFMATE-2						
Standard	2	✓	-	-	✓	4688124
CA	2	✓ (CA Valves)	-	-	✓	4688125
CA-TC	2	✓ (CA Valves)	-	✓	✓	4688126
CA-WTC	2	✓ (CA Valves)	-	✓ (Wireless)	✓	4688127
REFMATE-4						
Standard	2	✓	✓	-	✓	4688129
CA	2	✓ (CA Valves)	✓	-	✓	4688100
CA-TC	2	✓ (CA Valves)	✓	✓	✓	4688130
CA-WTC	2	✓ (CA Valves)	✓	✓ (Wireless)	✓	4688131



V1 06/19