

CC Series A2L

DUAL VOLTAGE VACUUM PUMPS



KEY FEATURES

- High performance A2L range
- Sparkproof switches
- Hard wired 5m Lead
- Dual Voltage
- Solenoid valve
- Easy Access oil drain



Model	CC-31 A2L	CC-141 A2L	CC-231 A2L
Part No.	JAV-1069-A2L	JAV-1065-A2L	JAV-1067-A2L
Suitability	All standard and A2L applications		
Stage	Double		
Ultimate vacuum	15 microns		
Free air displacement	40 l/m (1.4 CFM)	151 l/m (5.3 CFM)	251 l/m (8.9 CFM)
Power supply	Dual voltage 110/240 V 50Hz		
Motor size	1/4 HP	1/2 HP	2/3 HP
Power cord	IEC		
Oil capacity	140 ml	540 ml	620 ml
Intake fittings	1/4" SAE, 3/8" SAE and 1/2" ACME		
Weight	4.5 kg	11 kg	14.8 kg
Dimensions	265 x 105 x 220 mm	348 x 140 x 272 mm	380 x 160 x 285 mm

CC Series

DUAL VOLTAGE VACUUM PUMPS



Model / Part No.	CC-31	CC-141	CC-231
Suitability	All standard refrigerants. Non Hydrocarbon		
Stage	Double		
CFM	1.4	5.3	9
Ultimate vacuum	15 microns		12 microns
Free air displacement	40 l/m (1.4 CFM)	140 l/m (5.3 CFM)	230 l/m (9 CFM)
Power supply	Dual voltage 110/240 V 50Hz		
Motor size HP		1/3	2/3
Power cord	IEC		
Oil capacity (ml)	380	450	500
Intake fittings	1/4 SAE, 3/8 SAE and 1/2 ACME		
Weight	9.8 kg	12 kg	15.5 kg
Dimensions	330 x 135 x 255mm	350 x 135 x 255mm	380 x 160 x 285mm