



Velo-X Twin Cylinder Recovery Unit



The JAVAC Edge Velo-X. Our first recovery unit fully compatible with all A2L and A3 refrigerants. Industry leading recovery rates and JAVAC reliability giving our quickest and most efficient solution yet.

- R32 / R1234YF / HFC / HCFC / CFC / HFO / A2L / A3
- Lightweight complete with shoulder strap
- LED indicator showing recovery and machine status
- 5m hard wired cable and spark proof switch
- Dual gauge monitoring shows the tank and system pressures with integrated low pressure auto-off switch.
- Intelligent safety sensing
- Includes reusable mesh particulate filter for the suction port which can be easily cleaned or replaced

Recovery Rates (R410a)

Liquid	377kg per hour
Vapour	20kg per hour
Push / Pull	408kg per hour

Description	Part No.
Velo-X Twin Cylinder Recovery Unit	JAV-1424
Power supply	Universal Voltage 100-240VAC 50/60Hz
Motor size	1.25 HP
Motor Type	Variable Speed Brushless DC, 1500-3000 rpm
Maximum current	12.0 amps
Compressor	2 Cylinder Oil-less Reciprocating, Air Cooled
High Pressure Cutout (Manual reset)	550 PSIG
Operating Temperature Range	0 to 49 °C
Dimensions	370 × 245 × 325 mm
Weight	13,8 kg